


TINNED THW-2 GROUNDING WIRE



APPLICABLE STANDARDS AND TESTS

- ✓ ASTM B-1, B-3, and B-8, B-33
- ✓ UL83
- ✓ Spark tested at 7500 VAC

PRINT WHEEL

- ✓ KRIS-TECH WIRE CO. #XX AWG TYPE
TW OR THW OR THW-2 90C 600V
SUN RES (UL) OR TW C(UL)

VALUE ADD SERVICE

- ✓ Custom lengths and put-ups
- ✓ 12 available colors
- ✓ Wire paralleling and cabling
- ✓ Wire stripping
- ✓ Custom print legends and labels

SCOPE

Single conductor PVC (polyvinyl chloride) insulated, 600-volt dual rated THW-2, THW, TW. Suitable for power and lighting in residential, commercial, and industrial applications.

CONSTRUCTION

Conductors: The single conductors are tin coated.

Insulation: Concentrically applied PVC insulation rated at -25°C to 90°C, wet or dry locations and sunlight resistant.

IDENTIFICATION AND PACKAGING

The wire shall be identified by surface marking indicating the manufacturer, AWG size, voltage rating, UL symbol and type designation. 500 ft/spl. packed 4/box or 2500 feet/spl spools are standard.

Custom lengths, non-standard colors, AWG, and custom packaging are available by request.

AWG	Standard Number of Strands	Insulation (Mils)	Nominal Overall Diameter – Inches (standard strands)	Approx. Shipping Weight (Lbs./Mft.)
14	Solid or 19	30	0.13/0.14	18/19
12	Solid or 19	30	0.14/0.16	28/29
10	Solid or 19	30	0.17/0.18	41/42
8	Solid or 7	45	0.22/0.24	72/74
6	Solid, 7 or 133	60	0.28/0.31/0.33	105/107/112
4	7 or 133	60	0.35/0.39	160/167
2	7 or 133	60	0.41/0.45	250/265
1	19	80	0.49	324
1/0	19	80	0.53	398
2/0	19	80	0.58	496
3/0	19	80	0.63	611
4/0	19	80	0.69	755



SNAP FOR MORE INFORMATION

Spec: Tinned THW-2 Grounding Wire
Issued: 09/16/2024
Supersedes: 08/26/2024